

CAT® ENGINE REBEARING & RESEALING TOOLING – 416F / 420F

REPAIR OPTION: Engine Rebearing and Resealing

ENGINES: C4.4

MACHINE MODELS: 416F / 420F

Part Number	Quantity	Description
4C-5597		ANTI-SEIZE COMPOUND
366-1820	2	MANIFOLD ALIGNMENT PINS
377-2038	1	MANIFOLD ALIGNMENT PINS
370-8376	6	CAP KIT
9U-6198	1	CRANKSHAFT TURNING TOOL
5P-7306	1	HOUSING
5P-7305	1	ENGINE TURNING TOOL
136-4632	1	TIMING PIN (CRANKSHAFT)
268-1966	1	ADAPTER
364-9107	1	TIMING PIN (FUEL INJECTION PUMP)
278-4138	1	CAP KIT
276-1216	1	INJECTOR PIPE NUT TOOL
367-2771	1	WRENCH
298-5564	1	T40 TORX SOCKET
227-4389	1	E10TORX SOCKET
370-4657	4	ROCKER ARM SPACER
268-1968	1	PRY BAR
1U-5718	1	VACUUM PUMP
169-7372	1	FLUID SAMPLING BOTTLE
4C-4057	1	TUBE 7.9 MM (0.31 INCH) OUTSIDE DIAMETER
247-5377	1	TORQUE WRENCH
8T-3052	1	DEGREE WHEEL
1U-6396	1	O-RING ASSEMBLY COMPOUND
9U-6195	1	VALVE SPRING COMPRESSOR
268-1969	1	ADAPTER
276-1221	1	HEAD
342-9206	1	FRONT COVER ALIGNMENT TOOL
367-3534	1	OIL SEAL REMOVAL & INSTALLER TOOL
9U-7336	1	HOUSING
230-6284	1	TIMING PIN (CAMSHAFT)
9U-7324	1	INDICATOR BRACKET
7H-1942	1	DIAL INDICATOR
3S-3268	1	INDICATOR CONTACT POINT

CAT® ENGINE REBEARING & RESEALING TOOLING – 416F / 420F

REPAIR OPTION: Engine Rebearing and Resealing

ENGINES: C4.4

MACHINE MODELS: 416F / 420F

Part Number	Quantity	Description
7H-1940	1	UNIVERSAL ATTACHMENT
–	4	GUIDE STUDS (M8 X 100 MM)
–	–	LOCTITE 5900
–	–	LOCTITE 243
–	1	LOCKING PIN (8 MM X 85 MM) Ø
–	2	1/2 INCH DRIVE T50 TORX BIT
–	2	1/2 INCH DRIVE X 8 MM HEX DRIVE
–	1	DRILL BIT 3 MM (0.118 INCH) Ø
–	1	DRILL BIT 6.5 MM (0.256 INCH) Ø
–	1	LOCTITE 575
–	2	GUIDE STUDS (M16 X 115 MM)
–	2	GUIDE STUD (M8 X 70 MM)
–	–	LOCTITE 5900
–	2	GUIDE STUD (M8 X 90 MM)

BUILT FOR IT.™

cat.com

© 2017 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, BUILT FOR IT, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

