

Sullivan Palatek



BACKFILL TAMPER

Model	Net Weight (lbs)	Bore (in)	Stroke (in)	Blows per Minute	Waranty
SBT-6	40.0	1.5	5.5	800	1 Year

CHIPPING HAMMERS

The full line of 15 pound class Chippers can come with open handles and thumb triggers or heavy duty 4 bolt handles with internal triggers.

Model	Net Weight (lbs)	Bore (in)	Stroke (in)	Blows per Minute	Waranty
SCHO-2	13.0	1.125	2	2,300	1 Year
SCHO-3	14.0	1.125	3	2,200	1 Year
SCHO-4	15.0	1.125	4	1,800	1 Year
SCH-2	13.0	1.125	2	2,300	1 Year
SCH-3	14.0	1.125	3	2,200	1 Year
SCH-4	15.0	1.125	4	1,800	1 Year
SCH-11	11.0	1.125	2.375	2,550	1 Year



SCH-4

CLAY DIGGERS

Model	Net Weight (lbs)	Bore (in)	Stroke (in)	Blows per Minute	Waranty
SCD-30	30.0	1.75	3.375	1,550	1 Year
SCD-20	19.0	1.418	2.75	1,560	1 Year

PAVING BREAKERS

The line of paving breakers include 30, 40, 60 and 90 pound "T" handle tools, all with industry standard chuck sizes. They are all built from a proven market design, 4 bolt back threads, heavy duty side rod bolts and springs, forged alloy construction with removable chucks. Internal oilers on the 30, 60 and 90 pound breakers

Model	Net Weight (lbs)	Bore (in)	Stroke (in)	Blows per Minute	Waranty
SPB-90	92.5	2.625	6.0625	1,250	1 Year
SPB-60	67.0	2.25	4.0937	1,400	1 Year
SPB-40	42.0	1.73	5.75	900	1 Year
SPB-30	34.0	1.75	3.375	1,550	1 Year



SPB-60

ROCK DRILLS

Model	Net Weight (lbs)	Bore (in)	Stroke (in)	Blows per Minute	Waranty
SRD-75	61.0	2.625	3.22	2,250	1 Year
SRD-55	56.0	2.625	2.6875	1,650	1 Year
SRD-50	51.0	3.0	2.0	2,300	1 Year
SRD-30	29.0	2.4375	1.4375	2,700	1 Year
SRD-20	16.5	1.9375	1.89	2,300	1 Year



SRD-50

SPIKE DRILLS

Railroad spike drivers are the same design as the standard paving

Model	Net Weight (lbs)	Bore (in)	Stroke (in)	Blows per Minute	Waranty
SSD-90	89.5	2.625	6.0625	1,250	1 Year
SSD-60	64.0	2.25	4.0937	1,400	1 Year

breakers and have a special forged alloy striking dolly with an additional grease fitting for lower end lubrication.