

298 HYLAB HSL SERIES

230 ton (208.6 mt)
Lattice Crawler Crane

Link-Belt
CRANES

PRELIMINARY



ENGINE

- Mitsubishi 6-cylinder M670-T3 365 hp
- Hydraulic system consists of 7 pumps
- Hydraulic pilot-operated control valves
- Remote hydraulic oil cooler
- Full flow filtration

DRUMS

- Wide 35" front and rear drums
- Grooved for 28mm rope
- 55,000 available line pull, 554 fpm available line speed

LOWER

- Hook & pin side frames
- Completely sealed lower
- Front & rear carbody weights - fast attachment
- Full contact 48" shoes
- Two-speed travel
- Travel propel quick disconnects are anchored and angled for fast, low, effort installation

COUNTERWEIGHTS

- 160,000 lbs total upper counterweight
- HSL counterweight removal system lowers entire assembly to ground – no blocking required
- Variety of upper counterweight combinations
- 60,000 lbs total lower counterweight
- Lower weights mount on quick attach hooks

BOOM HOIST

- 25' live mast with flip for transport
- 22mm boom hoist rope with 20 part reeving

ATTACHMENT

- 60 ft to 300 ft main boom
- 30 ft to 90 ft fixed jib
- 190 ft + 200 ft luffing jib

Link-Belt Construction Equipment Company
Lexington, Kentucky | www.linkbelt.com

© Link-Belt is a registered trademark. Copyright 2006. All rights reserved. We are constantly improving our product and therefore reserve the right to change designs and specifications.
Litho in U.S.A. 10/06 491 #4330