



CAT® LIFT TRUCKS

With load capacities ranging from 2,500 to 36,000 lbs., Cat Lift Trucks product offerings consist of electric counterbalanced cushion and pneumatic tire lift trucks as well as internal combustion cushion and pneumatic tire forklifts. With a dedicated focus on quality, reliability and customer service, Cat Lift Trucks offers innovative material handling solutions.

EP4000



Class IV Internal Combustion Cushion Tire (LP Gas)

Model	Capacity (lbs)	Turning Radius (in)	Length (in)	Width (in)	Height (in)	Weight (lbs)
3,000-6,000 lb capacity LP Gas Cushion Tire						
2C3000	3,000	70	82	38	81	6,065
2C3500	3,500	71	83	38	81	6,450
2CC4000	4,000	73	86	40	81	7,010
2C4000	4,000	77.5	90.5	42	81.5	7,360
2C5000	5,000	79.5	92.5	42	81.5	8,155
2C5500	5,500	81	95	42.4	81.5	9,050
2C6000	6,000	82.5	96.5	42.4	81.5	9,480
2C6500	6,500	83.5	97.5	42.4	81.5	9,840
7,000-15,000 lb capacity LP Gas Cushion Tire						
GC35K	7,000	88	98.8	46.5	86.8	11,550
GC40K	8,000	90	100.4	46.5	86.8	12,280
GC40KSTR	8,000	82.3	94.9	46.5	86.8	12,470
GC45KSWB	10,000	92.1	103.1	46.5	86.8	14,265
GC55K	12,000	100.4	114.6	52	86.8	15,850
GC55KSTR	12,000	92.5	104.5	52	86.8	16,645
GC60K	13,500	101.2	116.1	56.7	88.8	19,310
GC70K	15,500	101.2	116.1	56.7	88.8	20,900
GC70KSTR	15,500	97.2	107.5	56.7	88.8	21,870
Model	Capacity (lbs)	Max Fork Height (in)	Length (in)	Width (in)	Height (in)	Weight (lbs)
8000-15,000 lb capacity LP Gas Cushion Tire						
GC40KPRHSTR	8,000	198.8	94.9	46.5	86.8	12,470
GC45KPRHSTR	10,000	198.8	103.1	46.5	86.8	14,265
GC55KPRSTR	12,000	179.5	104.5	52	86.8	16,645
GC70KPRH	15500	198.8	116.1	56.7	88.8	20,900
GC70KPRHSTR	15500	198.8	107.5	56.7	88.8	21,870

2C6000



Class 1 - Electric Counterbalanced

Model	Capacity (lbs)	Voltage (V)	Turning Radius (in)	Length (in)	Width (in)	Height (in)	Weight (lbs)
2,500-4,000 lb capacity 3 -Wheel Pneumatic Tire							
2ET2500	2,500	48	56.7	69.9	41.7	80.4	5,947
2ETC3000	3,000	48	60.9	74.3	41.7	80.4	6,520
2ET3000	3,000	48	65.2	78.6	41.7	80.4	6,627
2ETC3500	3,500	48	60.9	74.3	44.1	80.4	7,084
2ET3500	3,500	48	65.2	78.6	44.1	80.4	6,957
2ET4000	4,000	48	65.2	78.6	44.1	80.4	7,343
3,000-4,000 lb capacity Pneumatic Tire							
EPC3000	3,000	48	73.2	78.3	41.7	80.4	6,597
EP3000	3,000	48	78.1	82.6	44.1	80.4	6,503
EPC3500	3,500	48	73.2	78.3	44.1	80.4	6,906
EP3500	3,500	48	78.1	82.6	44.1	80.4	6,812
EP4000	4,000	48	78.1	82.6	44.1	80.4	7,175
3,000-6500 lb capacity Electric Cushion Tire							
E3000 36V	3,000	36	70.5	78	37	86	6,200
E3000 48V	3,000	48	70.5	78	37	86	6,200
E3500 36V	3,500	36	70.5	78	37	86	6,800
E3500 48V	3,500	48	70.5	78	37	86	6,800
EC4000 36V	4,000	36	72.5	81	39	86	7,400
EC4000 48V	4,000	48	72.5	81	39	86	7,400
E4000 36V	4,000	36	74.5	82	41.5	87	8,100
E4000 48V	4,000	48	74.5	82	41.5	87	8,100
EC22N2 36V	4,500	36	73.2	82	41.5	87	8,805
EC22N2 48V	4,500	48	73.2	82	41.5	87	8,805
EC25N2 36V	5,000	36	73.2	82	41.5	87	9,140
EC25N2 48V	5,000	48	73.2	82	41.5	87	9,140
EC25EN2 36V	5,000	36	77.3	85.9	41.5	87	9,350
EC25EN2 48V	5,000	48	77.3	85.9	41.5	87	9,350
EC25LN2 36V	5,500	36	77.3	85.9	43.5	87	9,680
EC25LN2 48V	5,500	48	77.3	85.9	43.5	87	9,680
EC30N2 36V	6,000	36	78.8	88.8	43.5	87	10,635
EC30N2 48V	6,000	48	78.8	88.8	43.5	87	10,635
EC30LN2 36V	6,500	36	79.5	88.8	43.5	87	11,090
EC30LN2 48V	6,500	48	79.5	88.8	43.5	87	11,090
5,000-6,000 lb capacity Pneumatic Tire							
2EPC5000	5,000	80	78.7	90.4	47.2	88.2	10,472
2EP5000	5,000	80	84.7	96.1	47.2	88.2	10,311
2EPC6000	6,000	80	78.7	90.6	47.2	88.2	11,530
2EP6000	6,000	80	84.7	96.3	47.2	88.2	11,303
2EP6500	6,000	80	84.7	96.5	51.2	88.2	11,876
8,000-10,000 lb capacity Pneumatic Tire							
2EPC8000	8,000	80	89.9	150.3	52.8	88.6	14,623
2EP8000	8,000	80	96.5	156	52.8	88.6	14,553
2EP8500	8,500	80	103.8	161.5	57.1	88	15,580
2EPC9000	9,000	80	89.9	150.3	57.1	88	15,637
2EP9000	9,000	80	96.5	144.1	57.1	88	15,547
2EP10000	10,000	80	96.5	156	57.1	88	16,402
2EP11000	11,000	80	103.8	161.5	57.1	88	17,476



Class IV - Internal Combustion Pneumatic Tire (LP Gas)

Model	Capacity (lbs)	Turning Radius (in)	Length (in)	Width (in)	Height (in)	Weight (lbs)
3000-7000 lb capacity Internal Combustion Pneumatic Tire						
2P3000	3,000	76.8	89	42	82.5	5,650
2P3500	3,500	78	90	42	82.5	6,070
2PC4000	4,000	79.5	92	42	83	6,750
2P4000	4,000	86.5	98	45.5	83	7,370
2PD4000	4,000	86.5	98	45.5	83	7,610
2P5000	5,000	87.8	100	45.5	83	7,990
2PD5000	5,000	87.8	100	45.5	83	8,210
2P5500	5,500	91.1	104	50	83	9,090
2PD5500	5,500	91.1	104	50	84	9,330
2P6000	6,000	93.7	107	50	84	9,400
2PD6000	6,000	93.7	107	50	84	9,640
2P6500	6,500	96	108	50	84	10,150
2PD6500	6,500	96	108	50	84	10,390
2P7000	7,000	96	110	51	84.5	10,340
2PD7000	7,000	96	110	51	84.5	10,590
8,000-12,000 lb capacity Internal Combustion Pneumatic Tire						
GP40N1	8,000	101	118	55.5	90.5	12,900
DP40N1	8,000	101	118	55.5	90.5	13,050
GP45N1	9,000	107	123	57.5	90.5	13,800
DP45N1	9,000	107	123	57.5	90.5	13,950
GP50CN1	10,000	109	125	57.5	90.5	14,950
DP50CN1	10,000	109	125	57.5	90.5	15,100
GP50N1	11,000	114	132.5	57.5	90.5	15,950
DP50N1	11,000	114	132.5	57.5	90.5	16,100
GP55N1	12,000	116	132	57.5	90.5	16,700
DP55N1	12,000	116	132	57.5	90.5	16,843
15000 lb capacity Diesel Pneumatic Tire						
DP70E	15,500	133.7	143.3	85.6	95.3	20,705
17,500-36000 lb capacity Diesel Pneumatic Tire						
P22000	22,000	157.5	168.9	99	114.8	34,613
P26500	26,500	159.8	172.2	99	114.8	37,412
P30000	30,000	163.8	178.1	102.4	116.5	41,293
P33000	33,000	179.1	190.2	102.4	116.5	40,411
P36000	36,000	189.6	198.6	103.7	116.5	42,395

5,500 LB CAPACITY PALLET JACK

This hand pallet truck has been engineered to provide long-lasting strength and versatility. Cat Lift Trucks can help you solve your tough material handling needs, with a full range of durable pallet trucks capable of handling your toughest applications.



2PD6000

Hand Pallet Truck

Model	Width (in)	Fork Length (in)	Lowered Height (in)	Raised Height (in)	Capacity (lbs)
A400002750	27	48	2.03	5.5	3,300
A400002748	27	48	2.92	7.67	5,500
A400002048	20.5	48	2.92	7.67	5,500
A400002036	20.5	35.5	2.92	7.67	5,500
A400002043	20.5	43.3	2.92	7.67	5,500