



ROUGH TERRAIN FORKLIFTS

Harlo has maintained leadership in this industry by working with many of the major tractor companies in America and by continually improving the design and quality of its forklifts and forklift components.

Harlo-designed mast assemblies are made out of steel, rolled to their specifications from Harlo-owned rolls. Their testing facilities set up for stability ratings of forklift units. Every mast produced by Harlo is put in a special test stand and cannot be shipped until the inspection is complete.

Harlo HP5000

Engine	Cummins QSB 4.5 electronic
Type	4 Cycle Diesel
HP	110@2500 rpm
Wheel Base	83
Fuel Tank	21.5
Drive tread width (in)	62
Underclearance (in)	15
Steer (2WD) (in)	68
Steer (4WD) (in)	68



Mast Options					
Capacity at 24 in load center	Lift Height (ft)	Over Height Lowered (in)	Carriage Width (in)	2WD Weight (lbs)	4WD Weight (lbs)
5,000 lbs	12 ft 2 Stg	110	48	11,697	11,947

Harlo HP6500/8500

Harlo HP6500/8500

Engine	Cummins QSB 4.5 electronic
Type	4 Cycle Diesel
HP	110@2500 rpm
Wheel Base	83.5
Fuel Tank	21.5
Drive tread width (in)	65.3
Underclearance (in)	15
Steer (2WD) (in)	68
Steer (4WD) (in)	73.6



Mast Options						
Capacity at 24 in load center (lbs)	Lift Height (ft)	Over Height Lowered (in)	Overall Extended (in)	Carriage Width (in)	2WD Weight (lbs)	4WD Weight (lbs)
6,500	15 ft 2 Stg	125	210	60, 72 or 84	13,122	13,458
	22 ft 3 Stg	125	300	60, 72 or 84	13,742	14,032
	28 ft 3 Stg	146	372	60	14,041	14,228
6,500 Free Lift	20 ft Stg	117	266	60, 72 or 84	13,840	14,130
8500	15 ft 2 Stg	125	212	60, 72 or 84	15,492	15,678
	16 ft 3 Stg	100	228	60, 72 or 84	15,648	15,724
	22 ft 3 Stg	125	100	60, 72 or 84	15,697	16,268
8500 Free Lift	20 ft Stg 3	117	266	60, 72 or 84	15,852	16,174