



THE BENDI ELECTRIC

The Bendi Electric Narrow aisle trucks are available with three stage tilting masts, with lift heights to 36 ft (11M). Quad masts are also available to 26 ft (7.29M), which gives the Bendi high stacking ability, while allowing the low mast height to work in highway trailers or travel through low doorways. Electric capacities range from 3,000 lbs to 4,500 lbs.



Model	Basic Capacity (lbs/kg)	Maximum Triple Mast Lift Height Available (in/M)	Maximum Quad Mast Lift Height Available (in/M)	Recommended Storage Aisle Size with 48" x 40" load (in/M)
B3/30 AC	3000/1363	360/9.14	NA	71/1800
B30AC	3000/1363	276/7.01	312/7.92	78/1981
B40AC	4000/1818	360/9.14	312/7.92	78/1981
B40VAC	4000/1818	360/9.14	312/7.92	72/1870
B55 AC	5500/2500	360/9.14	315/8	84/2.13
B55 AC HL	5500/2500	472/12	NA	84/2.13



THE BENDI I4 – LP GAS POWERED

Almost everything that makes the battery-powered Bendi the right choice for so many applications applies equally to the Bendi IC. Both are equally at home on the loading dock or in the warehouse. Both can go from trailer to plant floor to narrow aisle storage without staging. Both navigate narrow aisles that allow Bendi operators to move safely into tight spots that other forklifts cannot reach. The main difference is that our LP-Powered Bendi can be fueled in less than 5 minutes.

Model	Basic Capacity (lbs/kg)	Maximum Triple Mast Lift Height Available (in/M)	Maximum Quad Mast Lift Height Available (in/M)	Recommended Storage Aisle Size with 48" x 40" load (in/M)
B40i4	4000/1818	312/7.92	312/7.92	78/1981



LANDOLL DREXEL SWINGMAST

Nothing else measures up to the Landoll Drexel SwingMAST lift trucks. Their unique design enables drivers to turn only the mast assembly, not the entire truck. Aisles as narrow as 4 ½ ft (1.37m) allowing you to store more than ever, can be easily obtained. The versatile Landoll Drexel SwingMast gives you four trucks in one; performing like a conventional counterbalanced truck, a reach truck, a side loader and a turret truck. Models available in capacities from 3,000 lbs (1363 kg) to 12,000 pounds (5454 kg), with 3 or 4 stage masts with lift Heights to 30 feet (9.14M).



Drexel

Model	Basic Capacity (lbs/kg)	Power Source	Maximum Triple Mast Lift Height Available (in/M)	Maximum Quad Mast Lift Height Available (in/M)	Recommended Storage Aisle Size with 48" x 40" load (in/M)
SLT-30AC	3000/1363	Electric	272/6.90	312/7.92	56/1420
SLT-35AC	3500/1590	Electric	272/6.90	312/7.92	56/1420
SL-30	3000/1367	Electric	272/6.91	312/7.92	60/1500
SL-40	4000/1818	Electric	360/9.14	312/7.92	60/1500
SL-50	5000/2272	Electric	374/9.5	315/8.00	60/1500
SL-60	6000/2727	Electric	289/7.34	NA	66/1676
SL-80	8000/3636	Electric	281/7.14	NA	72/1829
SL-120	12000/5455	Electric	243/6.17	NA	78/1981
E-60-SL	6000/2727	LP Gas or Diesel	240/6.10	NA	72/1829

Drexel EX (Explosion Proof)

FL-40-EX	4000/1818	Electric	236/5.99		144/3658
FL-60-EX	6000/2727	Electric	234/5.94		144/3658



LANDOLL STAND-UP COMPACT

The LSC is a 3 wheel stand-up ride, compact, rear entry front loader, with a single poly rear drive/steer and poly load tires. It's a short turning radius, high visibility mast and compact design makes stacking and dock work easy and efficient. The low step height provides easy access on and off the truck for order picking and load checking.

Model	LSC25		LSC30
Capacity at 24" (600mm) Load Center	lb/kg	2,500/1,136	3,000/1,364
Truck Weight with Battery	lbs/kg	6,750/3,068	6,600/3,000
Travel Speed	Loaded	mph/kph	6/9.7
	Unloaded	mph/kph	7/11.3
Wheelbase - Mast Vertical	in/cm	34.6/88	40.6/103
Fork Length	in/cm	42/107	42/107
Operator Floor Height	in/cm	10.5/27	10.5/27
Gradeability Loaded/Unloaded	%	7/12	7/12