



MODEL SPECIFICATIONS	MODELS		
	3625	3635	3645
Engine			
Engine HP @ rated engine rpm	68 @ 2,200*	78 @ 2,200*	91 @ 2,200*
PTO HP @ rated engine rpm	55 @ 2,200*	65 @ 2,200*	75 @ 2,200*
SisuDiesel™ engine model	33 DT	33 DT	33 DTA
Cylinders and aspiration	3 - Turbocharged	3 - Turbocharged	3 - Turbocharged
Total displacement: in. (liters)	201 (3.3)	201 (3.3)	201 (3.3)
Fuel tank capacity platform: US gal. (liters)	29 (109.7)	29 (109.7)	29 (109.7)
Fuel tank capacity cab: US gal. (liters)	29 (109.7)	29 (109.7)	29 (109.7)
Clutch			
Type standard transmission (8x8 SynchroShuttle)	Dry single disc	Dry single disc	Dry single disc
Diameter: in. (mm)	12 (305)	12 (305)	12 (305)
Type Optional transmission (12x12 PowerShuttle)	Wet-Multi Disc	Wet-Multi Disc	Wet-Multi Disc
Transmission			
Type Standard Platform	8F x 8R MS	8F x 8R MS	8F x 8R MS
Type Optional Platform	12F x 12R PS	12F x 12R PS	12F x 12R PS
Type Standard Cab	8F x 8R MS	8F x 8R MS	8F x 8R MS
Type Optional Cab	12F x 12R PS	12F x 12R PS	12F x 12R PS
Brakes & Final Drives			
Final drives	Planetary	Planetary	Planetary
Brakes	Wet multi disc	Wet multi disc	Wet multi disc
PTO Type			
Type Standard Platform	Independent	Independent	Independent
Standard Speed Platform/Cab	540	540	540
Type Standard Cab	Independent	Independent	Independent
Optional Speed Platform/Cab	Shiftable 540/540E	Shiftable 540/540E	Shiftable 540/540E

MODEL SPECIFICATIONS	MODELS		
	3625	3635	3645
Hydraulics			
System type	Open center	Open center	Open center
Pump(s) type	Engine Driven Gear	Engine Driven Gear	Engine Driven Gear
Total flow: gpm (lpm)	22.4 (84.8)	22.4 (84.8)	22.4 (84.8)
Max flow @ remotes: gpm (lpm)	15.8 (59.8)	15.8 (59.8)	15.8 (59.8)
Remote Valves	2 standard	2 Standard	2 Standard
Three Point Hitch			
ASAE category	I-II	I-II	I-II
Extendable Lower Links	Option	Option	Option
Stabilizers	Telescopic	Telescopic	Telescopic
Lift capacity @ Hitch Point lbs. (kg)	5,512 (2,500)	5,512 (2,500)	5,512 (2,500)
*Manufacturers Estimate			
Weight & Dimensions**			
Rear tire used for measurement:	16.9R30	16.9R30	16.9R30
Wheelbase: in. (mm) 2/4wd	81.88 (2,080)	81.88 (2,080)	81.88 (2,080)
Overall length: in. (mm) 2/4wd	148 (3,759)	148 (3,759)	148 (3,759)
Min. overall width: in. (mm)	76 (1,930)	76 (1,930)	76 (1,930)
Height top of ROPS: in. (mm)	99 (2,515)	99 (2,515)	99 (2,515)
Height top of Cab: in. (mm)	101.18 (2,570)	101.18 (2,570)	101.18 (2,570)
Ground clearance @ front axle: in. (mm)	14.56 (370)	14.56 (370)	14.56 (370)
2WD platform approx. shipping weight: lbs. (kg)	5,071 (2,300)	5,071 (2,300)	5,071 (2,300)
4WD platform approx. shipping weight: lbs. (kg)	5,512 (2,500)	5,512 (2,500)	5,512 (2,500)
2WD cab approx. shipping weight: lbs. (kg)	6,174 (2,800)	6,174 (2,800)	6,174 (2,800)
4WD cab approx. shipping weight: lbs. (kg)	7,056 (3,200)	7,056 (3,200)	7,056 (3,200)
**Tire sizes will vary dimensions & weights			