

AGCO, Your Agriculture Company, is a premier manufacturer of agricultural equipment, providing high-tech solutions for professional farmers feeding the world. The company is dedicated to delivering superior customer service, innovation and quality. AGCO products are distributed in more than 140 countries worldwide.

AGCO FINANCE

At AGCO Finance, we understand that financing is as much a part of your purchase decision as the features and benefits of the product. So we're committed to providing the best means of acquiring the equipment you need, while allowing you to preserve other credit lines of operating capital.

See your authorized RoGator dealer for:

- Competitive Rates
- Comprehensive Financing
- Flexible Payment Schedules
- Flexible Terms
- Quality Service
- Leasing Options
- Virtually Unlimited Resources

AGCO ANSWERS

At AGCO, customer care isn't just a department. It's a commitment. Contact us with your questions, we'll do our best to answer them promptly or put you in touch with someone who can.

877-525-4384 or agcoanswers@agcocorp.com

SprayParts.com

When you purchase a RoGator, you get the backing and support of our world-class dealers who take productivity to heart. Combine that with our 24-hour-a-day parts network, and you have the absolute gold standard in dealer support. *SprayParts.com* is your 24/7/365 resource for a complete line of quality replacement parts and accessories.



See more at applylikeapro.com

© 2009 AGCO Corporation. AGCO® and RoGator® are registered trademarks of AGCO Corporation. CAT® is a registered trademark of Caterpillar, Inc. AGCO Corporation has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. AGCO Corporation is not responsible for differences between the specifications or illustrations contained in this publication and the actual equipment. Equipment produced by other manufacturers is shown in photographs in this brochure for the purpose of illustration only and is not intended as an endorsement of that particular equipment or its suitability. All rights reserved. AGCO Corporation, 4205 River Green Parkway, Duluth, GA 30096. RG09379 (09) 15 ADV O&B 37923-01 DS



SPECIFICATIONS

ROGATOR® FOR PRE- & POST-EMERGENCE APPLICATIONS | 984 • 984H • 1184 • 1184H • 1386



984 • 984H • 1184 • 1184H • 1386 | SPECIFICATIONS



RoGator® is a worldwide brand of AGCO Corporation.

SPECIFICATIONS COMMON TO ALL MODELS

HYDROSTAT						
Make & Model	Bosch Rexroth AA4VG					
Displacement	7.6 cu. in. (125 cc)					
WHEEL MOTOR						
Make	Sampo					
Model Front	BBC 05 with Parking Brakes					
Model Rear	BBC 05					
BRAKES						
Service	Hydrostatic Dynamic Braking					
Parking	Multiple Wet Disc on Front Wheel Motors					
FRAME						
Material	Flexible Modified Carbon Steel					
Shape	3 X 9" C Section					
Construction	Ladder-Style Bolted Cross Members					
STEERING						
Cylinders	Double-Acting					
Toe Alignment	Hydraulic Rephasing					
Turning Radius Center of Axle (2-wheel steer)	23 ft. (7 m)					
Optional GatorTrak (4-wheel steer)	13.5 ft. (4.1m)					
APPLICATION CAB						
Glass Area	60 sq. ft. (5.5 sq m)					
Floor Area	14 sq. ft. (1.3 sq m)					
Cab Suspension	Optional Air Ride Cab					
Radio	AM / FM CD with Weather Band / Satellite Ready					
HVAC	Automatic Temperature Control					
Filtration	Three-Level Activated Carbon					
Steering Wheel	14 inch Leather Wrapped					
Standard Seat	Air Ride Seat Suspension					
Optional Seat	Semi-Active Seat Suspension with Heated Seat Cushions					
AIR SYSTEM						
Compressor	Engine Mounted					
Governor	120 psi (8.2 bar)					
CFM	13.2 cfm (6.2 L/s)					
Reservoir	12.5 gal. (48 L)					
FLUID CAPACITIES						
Fuel	Hydraulic Reservoir	Engine Oil	Engine Coolant	Gear Box	Windshield Reservoir	
130 gal. (492 L)	60 gal. (227 L)	24 qt. (22.7 L)	30 qt. (32 L)	4.5 qt. (4.3 L)	1.6 qt. (1.5 L)	

984H

ENGINE	
Make/Model/Certification	Caterpillar C7 Tier III
Number of Cylinders	6
Horsepower	250 (186 kW) @ 2,100 rpm
Peak Horsepower	275 (205 kW) @ 1,850 rpm
Displacement	439 cu. in. (7.2L)
Torque	888 ft-lbs (1204 n-m) @ 1,400 rpm

984 • 1184 • 1184H

ENGINE	
Make/Model/Certification	Caterpillar C7 Tier III
Number of Cylinders	6
Horsepower	275 (205 kW) @ 2,100 rpm
Peak Horsepower	299 (223 kW) @ 1,850 rpm
Displacement	439 cu. in. (7.2L)
Torque	977 ft-lbs (1324 n-m) @ 1,400 rpm

1386

ENGINE	
Make/Model/Certification	Caterpillar C9 Tier III
Number of Cylinders	6
Horsepower	311 (232 kW) @ 2,100 rpm
Peak Horsepower	336 (251 kW) @ 1,900 rpm
Displacement	538 cu. in. (8.8L)
Torque	1105 ft-lbs (1499 n-m) @ 1,400 rpm

984H • 984 • 1184H • 1184

HYDROSTAT	
Make/Model	Bosch Rexroth Tandem AA4VG
Displacement	7.6 cu. in. (125 cc)

1386

HYDROSTAT	
Make/Model	Sauer Danfoss Tandem Series 90
Displacement	6.1 cu. in. (100 cc)

984H • 984 • 1184H • 1184

SPEED				
	1st	2nd	3rd	4th
	14 mph (22.5 kph)	18 mph (28.9 kph)	24 mph (38.5 kph)	33 mph (53.1 kph)

1386

SPEED				
	1st	2nd	3rd	4th
	13 mph (21 kph)	15 mph (24 kph)	17 mph (27 kph)	21 mph (34 kph)
	5th	6th		
	25 mph (40 kph)	36 mph (58 kph)		

984H • 1184H

ADJUSTABLE AXLE	
Outer Tube	8 in. X 8 in.
Inner Adjustable Tube	Reinforced 6 in. X 6 in.
Adjustment Range	120 in. to 152 in.
SUSPENSION	
Type	Variable Rate Leaf Spring
Fore and Aft Torque Rods	Rubber-Isolated Parallel Link
Rebound Control	Shock Absorber

984 • 1184 • 1386

ADJUSTABLE AXLE	
Outer Tube	8 in. X 9 in.
Inner Adjustable Tube	Reinforced 6 in. X 6 in.
Adjustment Range	120 in. to 152 in.
SUSPENSION	
Type	Air Spring
Leveling Valves	Haldex Height Control Valves
Fore and Aft Torque Rods	Rubber-Isolated Parallel Link
Rear Anti-Roll System	Modified Four Link
Rebound Control	Shock Absorber

