

All new 2012!



Boom

- Boom wear pads have Teflon pucks that lubricate boom sections (no grease)
- Available bi-fold on-board fly with 2°, 15°, 30° and 45° offsets
 - Over 25 tons (22.6 mt) capacity and one-load two-line lift procedures
- Available 10 ft (3.0m) fly is integral to on-board fly
- Available two 18 ft (5.5m) lattice extensions
- Maximum tip height - 250 ft (76.2m)

Carrier

- Outrigger position sensing (OSHA)

Operator's cab

- 20° tilt capability
- New gauge and control placement
- Link-Belt Pulse operating system
 - Rated capacity limiter (RCL)
 - Boom extend mode control (EMC)
 - Self-diagnostics

Superstructure

- 26,000 lbs (11.8 mt) counterweight
- Winch directional indication (OSHA)
- Access ladders and folding guardrails
- Larger access doors



RTC 80110

110 USt (100 mt) Rough Terrain Crane



All new 2012!

Designed with transport in mind

- Designed with transport in mind
- Boom and on-board fly can stay on for transport
- Tires stay on for transport
- Available counterweight and outrigger box removal
- 9' 10" (3.0m) width without outrigger boxes
- Assemble/disassemble in less than one hour




Link-Belt
C R A N E S

RTG 80110
110 USt (100 mt) Rough Terrain Crane