



When you need a lift, you know it must be a Genie. Genie sets the standard by which other lifts are judged. Simply put, Genie builds a better lift for every job. With four decades of experience, Genie provides the most advanced equipment in the industry the full line of the genie products, offers unmatched performance and reliability.



SCISSOR LIFT



NARROW AISLE MANLIFT



TELESCOPIC BOOM LIFT





Model	Working Height Max (ft)	Horizontal Reach (ft.)	Lift Capacity (lbs)	Power Source
Articulating Booms - Electric & Bi-Energy				
Z-30/20 N	36	21.5	500	48V DC
Z-30/20N RJ	35.2	20.6	500	48V DC
Z-34/22 DC	40.6	22.3	500	48V DC
Z-34/22 Bi-Energy	40.6	22.3	500	48V DC/Kubota 13.3 hp
Z-40/23N	46.5	22.8	500	48V DC
Z-40/23 RJ	46.5	22.8	500	48V DC
Z-45/25 DC & Bi	51.6	25.00	500	48V DC
Z-45/25J DC & Bi	51.9	25.1	500	48V DC

Model	Working Height Max (ft)	Horizontal Reach (ft.)	Lift Capacity (lbs)	Power Source
Articulating Booms - Diesel Engine				
Z-34/22 IC 2WD	40.6	22.3	500	Kubota gas or diesel
Z-34/22 IC 4WD	40.10	22.3	500	Kubota gas or diesel
Z-45/25 RT	51.10	24.7	500	Ford, Duetz or Perkins - gas or diesel
Z-45/25J RT	52.1	24.8	500	Ford, Duetz or Perkins - gas or diesel
Z-60/34	66.4	36.3	500	Ford, Duetz or Perkins - gas or diesel

Model	Working Height Max (ft)	Horizontal Reach (ft.)	Lift Capacity (lbs)	Power Source
Telescopic Booms				
S-40	46	31.8	500	Ford, Duetz or Perkins - gas or diesel
S-45	51	36.8	500	Ford, Duetz or Perkins - gas or diesel
S-60 X/ S-60 XC	64.4	50.10	500	Ford, Duetz or Perkins - gas or diesel
S-65	71.0	56.2	500	Ford, Duetz or Perkins - gas or diesel
S-80X	86	71.6	500/1000	Duetz, Perkins or Continental -gas or diesel
S-85	91	76.6	500	Duetz, Perkins or Continental -gas or diesel
S-100	106	75	750	Duetz or Perkins diesel
S-105	111	80	500	Duetz or Perkins diesel
S-120	126	75	750	Duetz or Perkins diesel
S-125	131.2	80	500	Duetz or Perkins diesel
SX-180	186	80	750	Duetz or Perkins diesel

Model	Working Height Max (ft)	Platform Width (in)	Lift Capacity (lbs)	Power Source
Slab Scissor Lifts				
GS-1530	21	2.5	600	24V DC
GS-1930	25	2.5	500	24V DC
GS-2032	26	2.8	800	24V DC
GS-2632	32	2.8	500	24V DC
GS-3232	38	2.8	500	24V DC
GS-2046	26	3.93	1200	24V DC
GS-2646	32	3.93	1000	24V DC
GS-3246	38	3.93	700	24V DC
GS-2669 DC	32	5.3	1500	48V DC
GS-3369 DC	39	5.3	1000	48V DC
GS-4069 DC	46	5.3	800	48V DC

Model	Working Height Max (ft)	Lift Capacity (in)	Platform Height
Aerial Work Platforms			
AWP-20S	26 ft 1 in	350	20 ft 1 in
AWP-25S	30 ft 10 in	350	25 ft 10 in
AWP-30S	35 ft 6 in	350	29 ft 6 in
AWP-36S	42 ft 5 in	350	36 ft 5 in
AWP-40S	46 ft 4 in	300	40 ft 4 in